

HDMI Extender, 1x HDMI Loop Out, 1x Cat5e/6 50m Output with IR and PoC 34MM-2K50

HDMI Extender with 1x HDMI input, 1x HDMI output and 1x CAT5e/6 extended output with bi-directional IR control and POC.

Features and Benefits

- » HDMI loop out port allows for cascading additional extenders or a local TV connection
- » Supports power over cable function POC. Only one power supply needed at the source. RX unit is powered by the Transmitter through the CAT5e/6 connection
- » 1x IR transmitter and 1x IR receiver included
- » Capacity for 1080p/60Hz HDMI1.3 to 50m.
- » 5V DC 1 Amp Power Supply included
- » Compact design for easy and flexible installation

Technical Data 34MM-2K50

	Transmitter	Receiver
Input	(1) HDMI	(1) CAT
Input Connector	(1) 19-pin type-A female HDMI	(1) RJ45
Output	(1) HDMI; (1) CAT	(1) HDMI
Output Connector	(1) 19-pin type-A female HDMI, (1) RJ45	(1) 19-pin type-A female HDMI
Control	(1) IR IN, (1) IR OUT	(1) IR IN, (1) IR OUT
Control Connector	(2) 3.5mm mini jacks	(2) 3.5mm mini jacks
General		
Transmission Distance	1080p@60Hz≤50m	
HDMI Standard	HDMI 1.3, HDCP 1.4 compliant	
EDID Management	Built-in EDID	
Power Supply	Input: 100VAC-240VAC, 50/60Hz; Output: 5VDC 1A	
Power	4W (Max)	
Consumption		
Work Temperature	-10-55°C	
Relative Humidity	10%-90%	
Dimensions (WxHxD)	66x16.8x66 mm	
Weight	Transmitter: 36g; Receiver: 38g	

1080p

