



For the Best

2020 Q4

New Products Catalogue



Matchmaster 2020 Q4 Catalogue



TV Mount Bracket Extra Large 100" Heavy Duty O4MM-TB11

- » Extra large heavy duty fixed design suitable for both flat and curved panel configurations from 60" to 100"
- » Heavy duty 100KG load rating to support large commercial screens
- » Open architecture design allows easy accommodation of larger recessed hubs for cable management
- » Automatic click in spring lock for added safety
- » 32mm slim profile to allow flush mounting to the wall



TV Tilt and Swivel Bracket 43"-100" O4MM-TB12

- » Swivel mount wall bracket 43-100 inch with full wall mounting back plate
- » Heavy duty 70 kg load rating supporting larger screens
- » Max 800mm off the wall allowing larger screens the ability to use all the available swivel.
- » Allows a VESA pattern up to 800 x 600
- » Built-In Level Adjustment: ensures perfect positioning
- » Post-Install Lateral Shift: makes it easy to centre TV on the wall, even with off-centre studs



TV Tilt and Swivel Bracket - Long Arm to 1015mm, 43"- 80" O4MM-TB13

- » 82-1015mm long extension arm provides a wide range of viewing angles
- » Swivelling Arms offer maximum viewing flexibility (makes every seat the best seat)
- » Heavy duty 50 kg load rating to support larger screens
- » Cable Management elegantly hides any cables that are attached to displays
- » For Most 43"-80" Flat Panel TVs
- » Quick-Release Latch locks and unlocks the display in place



RG11 Quad-shield Low Smoke Zero Halogen 305M Reel O6MM-E11QLSZH

- » An RG11 metre marked Low Smoke - Zero Halogen cable with quadshielding
- » Developed due to concerns about the fire hazards of the insulation and jacketing material
- » Meets requirements for smoke index, acid gas generation, halogen content, and toxicity index
- » Sold in a 305 metre reel

Matchmaster 2020 Q4 Catalogue



MicroUSB-B to USB-C OTG Patchcord

14MM-OTG1

- » MicroUSB-B male to USC-C male connection patchcord, 1m long. It allows connections between AVANT programmable amplifiers and an Android mobile device, for its use with ASuite app. The patchcord incorporates the OTG (On-The-Go) protocol, which allows its use without any additional special adapter or connector.



Terra mini Fibre Receiver 70dBuV output with dual SC/APC connectors 47-2400MHZ with built in WDM

20MM-ODO07H

- » Wide band mini Fibre Receiver for single wire Pay and FTA systems - 47-2400MHz
- » 70dBuV output per carrier
- » AGC based on RF signal output level
- » Robust die-cast housing providing high level screening
- » Can be powered either by RF output F-Connector or by local 3.5/1.3 mm DC jack (power supply sold separately) with 10-20V DC operating range
- » LED indication of RF level



IR Extender Kit for 3 rooms

34MM-IRKIT-3

- » Can be expanded further with additional 34MM-IR-RX IR receivers for extra areas and 34MM-IR-TX for additional components.
- » Wired IR for ultimate performance and reliability
- » Additional 34MM-IR4X units can be daisy chained many times to expand both the RX and TX functions.
- » RJ45 RX/TX allow IR distribution over CAT5/6 Structured Cabling. Add 34MM-IRMJ to accommodate emitters in the source location.
- » MySky compatible
- » Kit includes: 34MM-IRCM, 3x 34MM-IR-RX , 2x 34MM-IR-TX, 34MM-IR4X and SMPS12V1A-20R



HDMI 2.0 18Gbps Extender Splitter with 1x HDMI Loop Out and 4 x Cat6 Out 35m with IR and PoC

34MM-4K50-4

- » HDMI loop out port allows for cascading additional extender/splitters, or connecting a local TV.
- » Supports 'power over cable' function POC. RX units powered by the Splitter thru the CAT6 connection
- » 1 x IR Transmitter and 4 x IR receiver included (one for each RX unit)
- » Capacity for 4K/60Hz HDMI2.0 (18Gbps) to 35m with CAT6.
- » Digital audio extraction via S/PDIF RCA and analog audio extraction via 3.5mm socket

Matchmaster 2020 Q4 Catalogue



5MP HD Dome IP PoE Camera IP65 3.6mm Fixed Lens **50MM-CD001**

- » ONVIF 17.06 compatible for simple communication and mobile viewing
- » 5MP resolution 2592 x 1944 at 15 frames per second or 4MP at 25 frames per second
- » Fixed 3.6mm lens with a 1/2.8" Sony IMX335 Low light CMOS sensor
- » 3pcs 28Q Array IR Led, IR distance 30-35m
- » Supports RTSP/FTP/DHCP/DDNS/NTP/SMTP/NFS protocols
- » Supports H.265/H.264 video standards



5MP HD Dome IP PoE Camera IP66 2.8-12mm **Varifocal lens IK10 Vandal Rated** **50MM-CD005**

- » ONVIF 17.06 compatible for simple communication and mobile viewing
- » 5MP resolution 2592 x 1944 at 15 frames per second or 4MP at 25 frames per second
- » Fixed 3.6mm lens with a 1/2.8" Sony IMX335 Low light CMOS sensor
- » 3pcs 28Q Array IR Led, IR distance 30-35m
- » Supports RTSP/FTP/DHCP/DDNS/NTP/SMTP/NFS protocols
- » Supports H.265/H.264 video standards



matchmaster.co.nz
0800 AERIAL 237 425

Products may vary from images shown and all specifications are correct at time of printing